



Nor-Cal Office: +1 (510) 778-8388
 E-mail: info@lagoflooring.com
 23158 Bernhardt St, Hayward, CA, 94545

Washington, Florida Office: +1 (206) 629-4177
 E-mail: infowa@lagoflooring.com
 411 S Dawson St Unit D, Seattle, WA, 98108

LAGO AquaPro™ Water-Proof Floors Product Specification

Thickness	10MM 8mm Waterproof Core+ 2mm Super Acoustic Underlayment
Dimension	9-3/8" Width x 60" Length
Finish	LAGO Scratch Shield™
Wear Layer	AC4 Rating, EN13329, ≥4000 cycles
Texture	EIR - High Definition Embossed In Register
Edge Detail	4 Sides Painted Micro-Bevels
Click & Installation	Uniclic® / Angle-Angle
SQFT/CARTON	27.34
Radiant Heat	YES (*Below 90°F)
Swelling After Submersion	≤5%
Steam Mop	Approved
Resistance to Chemicals	Pass ASTM F925-13
Resistance to Bacteria	Pass, ISO 846-1997 Method C, Assessment of bacteria growth: 0
Slip Resistance	Class DS EN13893
Colorfastness to Light	ISO105-B02, Class: 6
Soluble Heavy Metal & PVC Contents Test	PVC Free, Heavy Metal Free, ASTM F963-16(Clause 8.3)
Sound Transmission Class STC	71
Impact Isolation Class IIC	70
WATER PROOF	100%
SAFTY	CARB2 Passed ; FloorScore Passed
LIMITED WATTANTY	Lifetime Residential /10 Years Commercial

© 2023. This technical data sheet was written by LAGO Flooring Inc. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to any third parties. The photographs used in this technical data sheet are for illustration purposes only.



Nor-Cal Office: +1 (510) 778-8388
 E-mail: info@lagoflooring.com
 23158 Bernhardt St, Hayward, CA, 94545

Washington&Florida Office: +1 (206) 629-4177
 E-mail: infowa@lagoflooring.com
 411 S Dawson St Unit D, Seattle, WA, 98108

LAGO AquaPro MAX™ Water-Proof Floors Product Specification

Thickness	15MM 12mm Waterproof Core+ 3mm Super Acoustic Underlayment
Dimension	9-3/8" Width x 60" Length
Finish	LAGO Scratch Shield™
Wear Layer	AC4 Rating, EN13329, ≥4000 cycles
Texture	EIR - High Definition Embossed In Register
Edge Detail	4 Sides Painted Micro-Bevels
Click & Installation	Uniclic® / Angle-Angle
SQFT/CARTON	19.53
Radiant Heat	YES (*Below 90°F)
Swelling After Submersion	≤5%
Steam Mop	Approved
Resistance to Chemicals	Pass ASTM F925-13
Resistance to Bacteria	Pass, ISO 846-1997 Method C, Assessment of bacteria growth: 0
Slip Resistance	Class DS EN13893
Colorfastness to Light	ISO105-B02, Class: 6
Soluble Heavy Metal & PVC Contents Test	PVC Free, Heavy Metal Free, ASTM F963-16(Clause 8.3)
Sound Transmission Class STC	73
Impact Isolation Class IIC	72
WATER PROOF	100%
SAFTY	CARB2 Passed ; FloorScore Passed
LIMITED WATTANTY	Lifetime Residential /10 Years Commercial

© 2023. This technical data sheet was written by LAGO Flooring Inc. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to any third parties. The photographs used in this technical data sheet are for illustration purposes only.