

<b>Lago SPC Plus™ 6.5mm Specification</b>	
<b>Dimension</b>	<b>7"/9" Width x 48"/60" Length</b>
<b>Thickness</b>	<b>6.5MM</b>
<b>Top-Layers</b>	<b>Lago Scratch&amp;Stain Shield™ Coating High Definition Decor Film</b>
<b>Core</b>	<b>5mm Rigid Core, 70% stone, 30% PVC. 100% Virgin Material</b>
<b>Underlayment</b>	<b>1.5mm Anti-microbial, Super Acoustic, IXPE Foam, 100% Virgin Material</b>
<b>Density</b>	<b>≥1900kg/m3</b>
<b>Packaging</b>	<b>22.47/23.67 Sqft/Carton</b>
<b>Texture</b>	<b>Real Wood Embossed</b>
<b>Bevels</b>	<b>4 Sides Painted-Bevels</b>
<b>Click &amp; Installation</b>	<b>Uniclic / Float</b>
<b>Radiant Heat</b>	<b>YES (*Below 90°F)</b>
<b>Static Load</b>	<b>1800 psi</b>
<b>Swelling After Submersion</b>	<b>0.00</b>
<b>Heat Exposure Resistance F1700</b>	<b>0.03%</b>
<b>Sound Transmission Class</b>	<b>STC=69</b>
<b>IIC</b>	<b>IIC=68</b>
<b>Water Proof</b>	<b>100%</b>
<b>Micro-Scracth Resistance</b>	<b>EN16094, Class B1</b>
<b>Abrasion Reistance</b>	<b>EN13329, ≥4000, Class AC4</b>
<b>Coatin Hardness Test</b>	<b>ASTM D3363-11, Class ≥8H</b>
<b>Adhesion</b>	<b>ASTM D3359-09, Class 5B</b>
<b>Resistance to Chemicals</b>	<b>ASTM F925-13: Pass</b>
<b>Colorfastness to Light</b>	<b>ISO105-B02, Class: 6</b>
<b>VOC</b>	<b>FloorScore™ Pass California 01350</b>
<b>Limited Warranty</b>	<b>Lifetime Residential /10 Years Commercial</b>

<b>Lago SPC Plus™ 8.5mm Specification</b>	
<b>Dimension</b>	<b>7"/9" Width x 48"/60" Length</b>
<b>Thickness</b>	<b>8.5MM</b>
<b>Top-Layers</b>	<b>Lago Scratch&amp;Stain Shield™ Coating High Definition Decor Film</b>
<b>Core</b>	<b>7mm Rigid Core, 70% stone, 30% PVC. 100% Virgin Material</b>
<b>Underlayment</b>	<b>1.5mm Anti-microbial, Super Acoustic, IXPE Foam, 100% Virgin Material</b>
<b>Density</b>	<b>≥1900kg/m3</b>
<b>Packaging</b>	<b>14.21/18.74 Sqft/Carton</b>
<b>Texture</b>	<b>Real Wood Embossed</b>
<b>Bevels</b>	<b>4 Sides Painted-Bevels</b>
<b>Click &amp; Installation</b>	<b>Uniclic / Float</b>
<b>Radiant Heat</b>	<b>YES (*Below 90°F)</b>
<b>Static Load</b>	<b>1800 psi</b>
<b>Swelling After Submersion</b>	<b>0.00</b>
<b>Heat Exposure Resistance F1700</b>	<b>0.03%</b>
<b>Sound Transmission Class</b>	<b>STC=73</b>
<b>IIC</b>	<b>IIC=75</b>
<b>Water Proof</b>	<b>100%</b>
<b>Micro-Scratch Resistance</b>	<b>EN16094, Class B1</b>
<b>Abrasion Resistance</b>	<b>EN13329, ≥4000, Class AC4</b>
<b>Coatin Hardness Test</b>	<b>ASTM D3363-11, Class ≥8H</b>
<b>Adhesion</b>	<b>ASTM D3359-09, Class 5B</b>
<b>Resistance to Chemicals</b>	<b>ASTM F925-13: Pass</b>
<b>Colorfastness to Light</b>	<b>ISO105-B02, Class: 6</b>
<b>VOC</b>	<b>FloorScore™ Pass California 01350</b>
<b>Limited Warranty</b>	<b>Lifetime Residential /10 Years Commercial</b>